

**Swingmaster**



**Eco Swingmaster**



**Swing PRO PLUS**



SPECIFICATIONS / FRAMES	Swingmaster	Eco Swingmaster	Swing PRO PLUS
DIMENSIONS	20" X 30" (508 X 762 mm), 30" X 40" (762 X 1016 mm), 40" X 60" (1016 X 1524 mm)	20" X 30" (508 X 762 mm), 30" X 40" (762 X 1016 mm), 40" X 60" (1016 X 1524 mm)	20" X 30" (508 X 762 mm), 22" X 28" (559 X 711 mm), 24" X 36" (610 X 914 mm), 30" X 40" (762 X 1016 mm)
TOP PROFILE	1.77" Aluminium	1.73" Aluminium	1.73" Aluminium
REAR PROFILE	Mitred corner	Safe corner	Safe corner
CORNERS PROTECTION COVER	Top 2 corners soft mitred corners, PET 0.02" waterproof ( rubber seal inside )	Top 2 corners soft/ safe mitred, round corners do not have sharp edges, PET 0.02" UV resistant (water wick) (rubber seal inside) and antireflex	Top 2 corners soft square mitred PET 0.04" UV resistant and antireflex,
BACKING WATERWICK/ GASKET	0.37" , PVC	0.37" , PP With waterwick/gasket directly in the	0.20" white fluted PP With waterwick/gasket directly in the
SPRINGS	Steel	Steel	Steel
NON-SLIP POSTER TAPE	Without	With poster tape for re-use around 100 times	With poster tape for re-use around 100 times
HEADER	N/A	Available by order seperatly	Available by order seperatly
PRINT ON PROFILE	1.10" (h)	1.10" (h)	1.10" (h)
PRICE	Economical	Budget	Competitive

