

DOUBLE SIDED SIDEWALK SIGNS WITH TOP OPENING DESIGN

Top opening Slide-in A Board is a practical product. Suitable for outdoor use. Available in Grey and Black finishes. Poster stands stable in between cover and backing. Rubber feet increase the product life as well as giving a clean finish to Slide-in A Board.

KEY SELECTION ATTRIBUTES

- Double-sided Pavement Sign with top opening slide-in design.
- Easy to use by sliding posters from snap opening top profile in between PET cover and PP backing.
- Suitable for outdoor use as it is heavy and rust-proof.
- One set includes double sided frames with top opening design, 2 anti-reflex PET poster covers, 2 PP backings, rubber feets, hinges, and scissors for keeping the system stable.
- Bottom profile of sandwich slide-in panel provide easy application.
- Rubber feet increase the product life as well as giving a clean finish to Slide-in A Board.
- Optional brochure baskets are not included, should be ordered separately.
- Silver and black colours in standard and various RAL colors available with antimicrobial powder coating.
- Standard Poster Thickness: 0.0039" 0.0078".
- Max poster thickness 0.16" when used without PP backer.
- In case a rigid board used as poster, max thickness is 0.28" without using U poster profile. If U profile is used, max 0.16" thick board can be attached onto the U profile.
- Packed in a single box with an easy-to-understand instruction sheet
- No tool assembly.





COLOURS IN STOCK





Silver

COLOUR OPTIONS

Black Anodised White - RAL 9003



SUITABLE FOR

Slide-in A Boards can be used for INDOOR and OUTDOOR applications, for signage needs in many locations like shopping centers, markets, groceries, hotels, offices airports, shops and stores, hospitals, schools, apartments and many more.

WATCH VIDEO



Watch video at our website www.mtdisplaysllc.com

FEATURES










EXPLODED VIEW




ARTI	CLES			Slide-in	pro	ttom ofile of the ndwich pan	el
						WEIGHT	PAC
GRAY	BLACK	EXTERNAL (x-y)	POSTER	COPY	Н	WITH PACKING	*/
HADCONOOSS	HADCODOOSS	24 24 11 11 20 24 11	22// 20//	24 00// 27 00//	45.20"	44.24411	25.50#1

		WEIGHT	PACKING SIZE				
GRAY	BLACK	EXTERNAL (x-y)	POSTER	COPY	Н	WITH PACKING	*WXHXD
UABSON0022	UABS0B0022	24.24" X 30.24"	22"X 28"	21.09" X 27.09"	45.28"	16.314 lbs	25.59" X 38.98" X 3.35"
UABSON0024	UABS0B0024	26.24" X 38.24"	24" X 36"	23.09" X 35.09"	45.28"	23.765 lbs	28.35" X 50" X 3.35"
UABSON0034	UABS0B0034	32.24" X 42.24"	30" X 40"	29.09" X 39.09"	49.21"	23.258 lbs	34.65" X 53.94" X 3.35"

TECHNICAL DRAWING





PHYSICAL DATA

Material

1.57" aluminium profile, PET anti-reflex poster cover, PP backing.

Poster Material & Thickness

0.0039" - 0.0078" for standard product. Max poster thickness 0.16" when used without PP backer. In case a rigid board used as poster, max thickness is 0.28" without using U poster profile. If U profile is used, max 0.16" thick board can be attached onto the U profile. Any non-standard poster thicknesses should be indicated with order.

Surface Finish

Natural silver-anodized, or black powder coated in standard and various RAL colors available with antimicrobial powder coating. Call for custom color requests.

Recycled Content

Up to 78% recycled content used.

Warranty

All products are guaranteed for 2 years by MT Displays with below conditions: **Warranty Conditions**

Installation Considerations

Slide-in A Boards are packed in a single box with an easy-to-understand instruction sheet. One set includes double sided frames with top opening design, 2 anti-reflex PET poster covers, 2 PP backings, rubber feets, hinges, and scissors for keeping the system stable. No tool assembly. Optional Brochure Baskets are not included, should be ordered separately.

Storage Conditions

Goods should be stored at 32°F to 77°F in a dry place. Store in the original package.

Design Considerations

Double-sided Pavement Sign with top opening slide-in design. Suitable for outdoor use with 22" X 28 ", 24" X 36", 30" X 40" poster sizes with a sight angle that stops passers-by. Easy to use by sliding posters from snap opening top profile in between PET cover and PP backing. Bottom profile of sandwich slide-in panel provide easy application. Rubber feets increase the product life as well as giving a clean finish to Slide-in A Board. Suitable for silk screen printing, max. letter height is 0.79".

Cleaning and Disinfecting

Clean your displays, with damp microfiber clothes, rinsed with simply water or warm, soapy or gentle shampooed water. Avoid using vinegar, abrasive, acidic, alcohol-based or heavy cleaners or cleaners containing Ammonia. Only after cleaning the product, if needed, simply apply disinfectant or sanitizer that is in compliance with your local guidelines and regulations.



PRINT TEMPLATES

Slide-in A Board - 22" x 28"

Document Size: 22.4" x 28.4" (Includes Bleeds) **Finished Size:** 22" x 28" (558.8 x 711.2 mm)

Slide-in A Board - 24" x 36"

Document Size: 24.4" x 36.4" (Includes Bleeds) **Finished Size:** 24" x 36" (609.6 x 914.4 mm)

Slide-in A Board - 30" x 40"

Document Size: 30.4" x 40.4" (Includes Bleeds) **Finished Size:** 30" x 40" (762 x 1016 mm)

INSTALLATION INSTRUCTIONS


Slide-in A Board / 1008625















Each Slide-in A Board includes (2 PET covers & 2 PP backings).



- Please inform the order number on the product or on the carton (e.g. 1/110001394-460) to the place that you have made the purchase if anyproblem with the product occurs.
- All rights reserved. All pictures, figures and writings are secured internationally by copy-right law. Infringements will be sued by civil and legal law.

This technical sheet's contents are all subject to update and modification at MT Displays' exclusive discretion. There is nothing official about this document. For final and legally binding information, please get in touch with the sales staff at MT Displays.

